

NPUT/OUTPUT CONNECTORS

Control Input/Output

LAN: RJ45 x1 (With PoE) 100 BASE-TX

RS232: RJ45 x1

RS422: RJ45 x2

CONTROL SIGNAL FORMAT

NDI® CONTROL

VISCA over IP

RS 232/ RS422: Baud Rate 2400 / 4800 / 9600 / 19200 / 38400

USER INTERFACE

Display: LED

Speed control: YES, 2 knobs (pan/tilt, zoom)

Zoom rocker: YES

Zoom ring ibn joystick: YES

Programmable function buttons: 6

CAMERA CONTROL

Maximum camera control: Max. 255 with multiple protocols including NDI/IP

Maximum serial connections:

RS232: 7 – RS422: 7

Key/Button illumination: Multi-colour LED

BUTTONS

Exposure Selection: Yes, Button

One push White balance: Yes, Button

Backlight control: Yes, Button

Display status of WB, Iris, Gain, Shutter, Focus: Yes

White balance model selection: Yes, Button

R, B, Gain: Yes, Knob

Iris Adjustment: Yes, Knob

Shutter Speed: Yes, Knob

Focus mode selection: Yes, Button

One push auto focus: Yes, Button

Manual focus: Yes, Knob

GENERAL

Power input: DC 12V, PoE (Power over Ethernet), Power via RS232/RS422 port

Current: 3W

Operating Temp: 0-40 (°C)

Dimensions: 278x132x99.5mm

Notes: Not all features are available on all control protocols