

## VIDEO FORMATS

(HD) 1080p 23.98, 25, 29.97, 50, 59.94

(HD) 1080i 25, 29.97

(HD) 720p 50, 59.94

## VIDEO INPUT

1 x 3G-SDI, SMPTE-259/292/296/424 (Level A / Level B)

1 x HDMI Standard Type A connector

HDMI v1.4a, RGB or YCbCr

## VIDEO OUTPUT

1 x 3G-SDI, SMPTE-259/292/296/424 (Level A)

1 x HDMI Standard Type A connector

HDMI v1.4a, RGB or YCbCr

## AUDIO DIGITAL

2-Channel, 24-bit SDI embedded audio,  
48 kHz sample rate, synchronous

2-Channel, 24-bit HDMI embedded audio,  
48 kHz sample rate, synchronous

## AUDIO ANALOG

3.5mm Microphone headset input / output

## VIDEO CODEC SUPPORT

Realtime, ultra-low latency, full-bitrate NDI  
(i-frame)

## DISPLAY

Internal 35x5 tri-colour LED display for  
information and tally indication

## NETWORK INTERFACE

10/100/1000 Ethernet (RJ-45) with PoE  
(Power over Ethernet)

Embedded web configuration panel for  
control and firmware updates

#### USER INTERFACE CONTROLS

Network settings

Video settings

Tally settings

Audio and Comms settings

#### EXTERNAL TALLY

3.5mm 2 position +5v tally connector

SIZE (W x D x H)

150x105x21mm

WEIGHT

0.3Kg

## POWER

100-240V, 50/60 Hz Universal Input, +5-18V DC7W Max

Power over Ethernet (PoE) 802.3af/at