

CAMERA

IMAGE SENSOR

1 / 2.8 inch CMOS 2.13MP

LENS

4.3-129mm

OPTICAL ZOOM

30x

DIGITAL ZOOM

12x

HORIZONTAL ANGLE OF VIEW

63.7° (W) – 2.3°(T)

APERTURE

F1.6 (W) – F4.7 (T)

MIN. ILLUMINATION

Color: 0.01 lux (F1.6, AGC on, 1/30s, High sensitive mode), 0.1 lux (F1.6, AGC on, 1/30s, Normal sensitive mode)

SHUTTER SPEED

1/1 – 1/10000s

FOCUS

Auto, Push, Manual

WHITE BALANCE

Auto, Indoor, Outdoor, Manual, OPW, ATW

EXPOSURE

Auto, Manual, Shutter/Iris Priority

BACKLIGHT COMPENSATION

YES

MECHANICAL

PAN MOVEMENT

Horizontal: $\pm 350^\circ$ continuous pan (Zoom Adaptive Speed Range: 0.05 $^\circ$ – 100 $^\circ$ /S)

TILT MOVEMENT

Vertical: +90 $^\circ$ to -30 $^\circ$ (Zoom Adaptive Speed Range: 0.05 $^\circ$ – 50 $^\circ$ /S)

PRESET POSITIONS

128 (Speed adjustable: Up to 150 $^\circ$ /s)

PRESET SPEED

0-5 Level adjustable

ENVIRONMENTAL

Indoor

OPERATING TEMPERATURE

-10 – +50 (°C)

OPERATING HUMIDITY

≤80%

VIDEO INTERFACE

VIDEO OUTPUT

NDI /HDMI /SDI

VIDEO FORMATS

1080p 60, 59.94, 50, 29.97, 25

1080i 60, 59.94, 50

720p 60, 59.94, 50, 29.97, 25

AUDIO I/O

3.5mm Audio In (Stereo)

3.5mm Audio Out (Stereo)

CONTROL INTERFACE

IP PTZ CONTROL

NDI Control (auto configuring)

SERIAL PTZ CONTROL

2x RJ45: RS232/RS422/RS485

SERIAL CONTROL PROTOCOL

VISCA / Pelco D

POWER & DIMENSIONS

POWER INPUT

12v DCm, PoE+ (IEEE 802.3at)

DIMENSIONS

160x178x220mm

WEIGHT

2.0Kg

NETWORK

VIDEO COMPRESSION

Full NDI – i-frame high quality low latency NDI for production

NETWORK PROTOCOL

NDI – Discovery, configuration and control

WEB CONTROL INTERFACE

Full control via Web/Mobile UI including Scene presets